



Mono inverter DC

AGBX9RL 9.000 class A/A

AGBX12RL 12.000 class A/A

MODEL		AGBX9RL	AGBX12RL
Cooling capacity (min~max)	W	820-3370	880 - 4040
Cooling capacity (min~max)	BTU/h	2795 - 11500	3000- 13800
Heating capacity (min~max)	W	820-3460	880-4160
Heating capacity (min~max)	BTU/h	2800- 11800	3000- 14200
Power supply	V-Hz-Ph	230-50-1	230-50-1
Type of refrigerant		R410A	R410A
Power input cooling (min~max)	W	180-1290	210 - 1460
Power input heating (min~max)	W	170-1210	190 - 1360
Dehumidifying	L/h	1	1,1
Air circulation	m ³ /h	400/450/500	380/440/550
Body size I.U	mm	710x250x189	790x275x196
Body size O.U.	mm	780x540x250	780x540x250
Weight I.U./O.U.	Kg	7/29,5	8/30
Noise max I.U./O.U	dB(A)	36/54	42/54
Suction pipe	In	3/8"	3/8"
Delivery pipe	In	1/4"	1/4"
Max. refrigerant pipe length	m	20	20
SEER		5,5	5,4
Energy eff. class		A	A
Annual energy consump.	kWh	455	555
SCOP		3,4	3,4
Heating performance class		A	A

